Earthquake Early Warning Instrumentation and Efficient Workflows

Abstract

To optimize earthquake early warning (EEW) systems, much can be learned from existing and industry proven EEW solutions and how they can be efficiently deployed with high quality ground motion seismic stations capable of delivering the highest fidelity and low latency data sets to the processing data centers' detection algorithms. Specifically, public safety EEW systems require strict service level agreements (SLA) with regards to overall uptime, prompt arrival of high quality data, and issuance of accurate and timely warnings. This can only be achieved via the proper definition and selection of sensors, dataloggers, power systems and communication systems. Also, when planning EEW Networks it is important to consider the end-to-end workflow, from system definition and roll-out, through to network operation, maintenance and ongoing validation to ensure the system continues to satisfy its mandate. Deployment of an EEW system can represent a significant challenge to monitoring agencies, but leveraging proven implementations and technology partners can greatly reduce the associated risk and implementation timeline.











Strong Motion

Telemetry



Timely

Quality Data

Discussion

Richer Catalog of Events to Inform Science

Complete Data Set

Combined Strong & Weak Motion Instrument

The selection of instrumentation is critical especially when the seismicity amplitude range at a site is unpredictable

- ★ Deploy stations with both a low self-noise seismometer and an accelerometer with a high clip level to maximize dynamic range
- * A rich event catalog, produced via broadband monitoring with low noise seismometers, allows improved fault delineation for seismic hazard mitigation
- **★** To minimize the development cost, consider integrated units that have the added benefit of simplifying the installation with one hole to dig, a single cable, and which the mutual alignment is guaranteed by the manufacturing process

Figure 1: On the left is an image of the Cascadia 120 Slim Posthole sensor, which combines a seismometer and a class A accelerometer. On the right is a plot of the self-noise, clip level and dynamic range of Cascadia 120 Slim and sample event SDECTRA. (John F. Clinton, Thomas H. Heaton Potential Advantages of a Strong-motion Velocity leter over a Strong-motion Accelerometer. Seismological Research Letters 2002;; 73 (3):





Turn-Key



Complete Datasets Redundant Data Processing

End-to-End Waveform Data Delivery

- ★ Dual, active-active telemetry routes from each monitoring station
- ★ Multiple, geographically redundant data centers, each independently receiving station data ★ Dual, redundant acquisition and processing tool chains within each data center



Figure 2: Mission-critical systems requiring multiple layers of redundancy (8 in the example) to achieve maximum data completeness may be implemented efficiently and cost-effectively with NP protocol multicasting

Timely Alerts **Robustness and Efficiency**

daptable data acquisition protoco

EEW systems perform best when using protocols that provide the right configurability to optimize key network performance metrics.

- ★ UDP-based data acquisition benefits from less packet header overhead vs TCP (>20% increase in transmitted data when using TCP/Seedlink)
- * System provides the ability to prioritize the transmission of live packets over packet retransmissions
- + IP multicasting provides support for high availability / redundancy in streaming architectures without the cost of additional network bandwidth
- ★ Data transmission can be throttled to protect against saturation of bandwidth-constrained telemetry links, and ensure capacity for command and control traffic
- ★ Data latency can be minimized by reducing packet size

Figure 3: The plots show the significant bandwidth improvement of using Nanometrics NP Protocol over UDP to 250 reduce bandwidth usage and latency.



Maximize Real-Time Waveform Availability **Data Delivery Stress Testing** End-to-End peak data delivery simulation

Heavy shaking associated with large earthquakes results in sudden spikes in bandwidth demand. Confidence in EEW system performance during these events may be maintained by simulating large earthquakes using appropriate fleet management tools and system performance dashboards.

 \star Modify the data compression of multiple stations in a single operation. **★** Evaluate acquisition performance via data availability and latency performance dashboards

Apolioserver		Apply Configuration			nanor
ealth Waveform Availability	Main	Apply configuration			Help cent
onfiguration Firmware Manage Av	vailable	Apply configuration on 2 selected	ed instruments.		
		Primary sample rate (Hz) :	<leave unchanged=""></leave>	~	on Commit Configuration Re
		Primary frames per packet :	3	~	
Station Instrument ID	State	Primary sample encoding :	<leave unchanged=""></leave>	~	y sample Input Range Mode ng
CN.NMX02 titanSMA_1145	✓ C	Mode (a) :	<leave unchanged=""></leave>	~	2g
CN.NMX03 titanSMA_1146	✓ c				2g

Figure 4: The image on the left shows the Apollo Server Fleet Management interface for batch configuration of multiple stations, which may be used to execute a network bandwidth stress test. The image on the right shows the Apollo Server dashboard for monitoring acquisition system performance, which presents data completeness and latency over time.

Mananometrics

David Easton (<u>davideaston@nanometrics.ca</u>), Michael Perlin, Nicholas Pelyk, Michael Laporte 3001 Solandt Rd, Kanata, ON K2K 2M8

Data path redundancy may be implemented at each stage to maximize data completeness



		SeedLink Latency	
66 <u>6</u> 6	9. 66	9 66 66 66 66 66 66 66 66 66 66 66 66 66	
0.3 0.4 0.5 Latency (s)	0.6 0.7 0.8 0.9	1 0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 Latency (s)	
		2 (s) 1	

Time Carias Only All Channels	Con	Canada Channela	tion: 2021 06 15 02-04:44 202 - 2021 06 16 02-04:4	4 202	
Time Series Only All Channels	Sea	: Search Channels	2021-06-15 02:04:44.202 - 2021-06-16 02:04:4	4.202 •	
Channel 💙	Availability with A	rage Latency 💙			
C3.11S1.01.BHX	>99%		1 1 1	- I II I	
C3.11S1.01.BHY	>99%		1	1	
C3.11S1.01.BHZ	>99%	·			_
C3.12S1.01.HHX	83%				
C3.12S1.01.HHY	67%	H	-	4	
C3.12S1.01.HHZ	>99%				
C3.2S1.L1.HNX	95%				
C3.2S1.L1.HNY	95%		⊷ ⊷		
C3.2S1.L1.HNZ	91%			1	
C3.2S2.01.HHX	>99%				
C3.2S2.01.HHY	>99%				
C3.2S2.01.HHZ	>99%				
C3.6S1.00.HHE	>99%				-
C3.6S1.00.HHN	>99%				-
C3.6S1.00.HHZ	>99%				

 It is important to quickly demonitoring of instrumenta ★ Simple Network Manage network uptime metrics ★ Integration is simplified others.
Figure 5: Centaur and TitanS the left, provide SNMP suppor screen capture on the right sl how state-of-health information be integrated into custom dashboards to monitor any a of system performance.
Operators should be allow and risk of delivering EEW ★ High fidelity and low late ★ Network security with si ★ Pre-configured power sy ★ Services for station site s
Figure 6: These photos sh turn-key strong motion sys provided by Nanometrics f EEW networks.
Conclus
Earthquake Early Warning s described a number of key enable organizations to mo Redundant Communication supporting workflows that e Delivery Stress Testing to er most.

Maximum Uptime **Enhanced Monitoring** Norkflow Automation

determine if equipment is online/offline; a common interface for health ation and networked devices using industry standard tools is powerful.

ement Protocol (SNMP) enabled network devices allow operators to easily track

l by using industry-standard monitoring tools such as Nagios®, SolarWinds®, or



aspect



Centaur

MN nanometrics

. ¹001. 1

T.



Standardize Deplovments **Turn-Key Solutions** Field proven Strong Motion Station

ved to focus on their program's core vision and mission and reduce the effort ' systems by using turn-key solutions that deliver key capabilities

ency data acquisition

- site-to-site encrypted virtual private networks
- systems with battery back-up and charging systems
- selection and field installation







sion

systems are critical to seismic loss mitigation programs. In the above, we ^r considerations when designing a system and how industry proven tools can ore easily implement EEW systems that will deliver Complete Data Sets via ns, with Robustness and Efficiency. Also described is the importance of the enable Enhanced Monitoring and continuous validation via periodic Data ensure the systems will deliver at the critical moment when they are needed